

HYOSUNG

7600XLD

SPECIFICATIONS

DIMENSION

- Height: 54.4"
- Width: 28.4"
- Depth: 40.6"
- Weight: 1,978 lbs.

ENVIRONMENTAL

- Temperature: 32°F – 104°F (0°C~40°C)
- Humidity 25% – 85%

SOFTWARE

- Microsoft Windows® 7
- Windows10 ready

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method – Touch screen
- Privacy Filter – 15" filter
- PIN Pad – PCI compliant
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant

MEDIA TECHNOLOGY

- **Dispense**
 - Configurable denominations up to 4 cassettes
 - 3,000 notes per cassette
 - Bundle present, bundle retract
- **Cash & Check InModule (CCIM)**
 - Maximum capacity 50 checks/cash per bundle per transaction
 - Check cassette capacity 2000 note (CCIM)
 - Cash cassette capacity 2000 note (CCIM)
 - Reject and retract capability

SECURITY

- Safe: UL291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- Security camera

SERVICING

- Rear access
- State of health indicators across

PRINTER

- 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

solutions@ftsius.com | 877.350.9055 | www.FTSIUS.com

