

Full Function Island Drive-Up ATM

Features

Maximum Reliability

Monimax 7800IA is designed to provide 2nd to none reliability in the market with highest uptime and with minimum maintenance needs. You won't have to worry about replacing the parts of sudden breakdowns because the Monimax 7800IA is designed to run for a very long time, problem-free.

Environment Stewardship

With quality comes also responsibility. Monimax series are equipped with energy saving features like low energy LCD and long lasting ATM parts with minimum implications to the environment. Deposit automation feature also saves tons of paper over time, giving you the power to build your image as an earth friendly company.

Flexibility

Monimax series are designs with open architecture platform allowing for easy future upgrades and module modifications. Module design is one of ways in which we are trying to save out customers' cost and provide maximum convenience. Monimax 7800IA can also be easily upgraded to offer deposit automation should an institutions decide to implement the technology in later period.

Ultimate Functionality

Monimax 7800IA offers ultimate functionality featuring bill payment, funds transfer, mobile top-up in a highly user friendly interface for maximum convenience and very easy transition.

Maximum Protection

Complying to standards in various regions worldwide, Nautilus Hyosung offers advanced security measures while highly secured integrity of the Monimax 7800IA prevents any attempted security breaches from occurring. Monimax 7800IA is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



System Platform

- Microsoft Window 10
- Hyosung Moniplus™ XFS

Customer Interface

- 15 inch or 19 inch display with touch screen (Sunlight viewable optional)
- 4 x 2 Function keys (optional)
- Lead-through indicator
- PIN Pad – PCI compliant
- Card Reader – EMV Ready
 - Dip, Motorized hybrid
 - EMV Level 1, 2 compliant
 - Anti-skimming device
- Contactless card reader (RF option)
- Audio – speaker / earphone jack

Servicing

- Front access (Rear access optional)

Printer

- Receipt printer : graphical thermal printer
- E-journal printer or direct thermal line printing

Media Technology

- Cash dispenser
 - Maximum fill level 345 mm per cassette
 - Up to 5 cassettes
 - Bundle present / retract
 - Note by note rejection
 - Automatic shutter
- Cash and Check depository (Single Slot)
 - Maximum fill level 227mm per cassette
 - Up to 75 notes and checks mixed bundle deposit per transaction*
 - 2 cassettes
 - Reject retract capability
 - ECB article 6 compliant
 - 4-way cash and check scanning & printing

Security

- Safe: UL291 Level 1, CEN safe
- Lock: Electronic lock, Mechanical combination lock, KABA Mas cencon lock
- Sensor: Alarm (Heat & Seismic), Door sensor
- Privacy filter (optional)
- Anti skimming, Anti card trapping, Anti shimmming, Anti cash trapping
- Security camera (Face & Hand)
- MoniGuard endpoint security software

Additional Features

- Barcode reader
- Proximity sensor
- Air-conditioner, Heater (option)
- Video Conference (option)

Power Supply

- AC 100V~240V, 50 ~ 60Hz

- Backup battery

(Reserving last transaction & safe)

Environmental Conditions

- Temperature : 0°C ~ 55°C (32°F ~ 131°F)
- Humidity : 10% ~ 100%

Dimensions

- Height: 1,494mm (58.8 inch)
- Width: 1,060.7mm (41.8 inch)
- Depth: 1,000.3mm (39.4 inch)
- Weight: 1,098kg (2,420 lbs.)

* Subject to note quality and other variables.

※ Internal Components may change with introduction of new technology. Hyosung TNS reserves the right to change the specifications of this ATM to accommodate the changes in technology.

